

INSAI

de

15

20

a

09-67-0210

5

10

15

25

SECRET

a sufficiently meet the requirements of receiving a ~~great~~ ^{large} amount of data streams with high bit rates in real time and
r ^{performing} ~~doing~~ reproducing processes of the multimedia information
a represented as image data, those reproducing processes
5 ^{including} ~~containing~~ a fast feed, a stop, and a reverse like reproduction of a video disk, for example.

SUMMARY OF THE INVENTION

It is an object of the present invention to provide a system for transferring multimedia information in
10 a system ^{including} ~~configured~~ of a multimedia server, CSS servers, and clients ^{the} ~~which~~ system ^{being} ~~is~~ arranged to simplify transmitting processes between the multimedia server and the CSS server and receiving processes between the CSS server and ^{to} ~~the~~ client and solve a bottleneck in connection
15 with a network between the CSS server and a plurality of clients for the purpose of keeping the data transfer quick and efficient.

According to the present invention, a multimedia information transfer system includes a multimedia server
20 and a client server system coupled with the multimedia server through a network so that the multimedia server transfers data to a server and clients of the client server system, the multimedia server having means for storing and reproducing data streams of the multimedia information, the
25 client having means for requesting the multimedia server to output data and storing the transferred data and means for displaying the data concurrently when storing the data.

According to an aspect of the present invention, the multimedia server operates to divide the multimedia information into N data blocks (N is an integer of 2 or more), each of which contains n data units (n is an integer of 1 or more), and sequentially transfer the data units to the server of the client server system on ~~each~~ ^{the} data ~~block~~ ^{blocks} ~~basis~~. Then, the client server system operates to transmit the data block containing n data units to the client for requesting the server to output the data.

Further, according to another aspect of the present invention, each network node of the multimedia server and the server and the clients of the client server system has network addresses dedicated for ~~receive~~ ^{the receipt} and ~~transmission~~ ^{of data}. The multimedia server and the server of the client server system, which ~~are served as~~ ^{transmit} transmitting the multimedia information, have their own matrix tables each for managing a receiving status and a process request status on the receiving side and operate to set the request from the receiving side to a field of the matrix and transfer the data based on the status.

According to another aspect of the present invention, the client ~~for~~ ^{receives data} requesting the process ~~is just~~ ^{required to receive} at the address defined on the receiving side the multimedia information, which is ~~the result~~ ^{being divided} processed by the multimedia server ^{in a manner to divide} ~~the data~~ ^{transferred in groups} into N data blocks and ~~transfer each group~~ of n data units in each data block, and ~~to set~~ a group of n data

a
being sent
units, to the defined address. Further, the client provides
a function of displaying the streams of the multimedia
a
information concurrently ^{while} ~~when~~ storing the streams. The ^{of data}
a
client enables ^{Concurrent Storage of data} ~~to store~~ and display, the streams ~~at a time~~
5 so that the client, by itself, can control a fast feed, a
stop, a reverse, and a play in real time.

The multimedia server has a matrix table for
managing a process requesting status from the side for
requesting the process and a receive status for the
10 processed result data for each service. When the side for
requesting the process operates to set the process
requesting status and the receive status to the matrix
table of the multimedia server, the matrix table reads
these statuses in sequence and sets the statuses to the
15 proper fields for the matrix table. Hence, the multimedia
server for providing the service is capable of transmitting
the processed result data for the services of the CSS
server and the clients as viewing the status of the matrix
table independently of the update of the matrix table.

20 Further, according to another aspect of the
present invention, as mentioned above, the data transfer is
executed between the CSS server and the client. Further,
the status management of the matrix table and the
transmission of the processed result data are allowed to be
25 executed by the device for providing the multimedia server
and the CSS server with the services. Hence, the
multimedia server, the CSS server, and the client are
a
capable of doing their ^{performing} processes independently of one

007260-4559960

another and the two former servers can meet the request from the client and transfer the processed result data.

BRIEF DESCRIPTION OF THE DRAWINGS

These and other objects, features, and advantages of the present invention will become more apparent upon a reading of the following detailed description and drawings, in which:

Fig. 1 is a block diagram showing an arrangement of a system for transferring multimedia information according to an embodiment of the present invention;

Fig. 2 is a view showing a format of a received data status for a client;

Fig. 3 is a view showing a format of a received data set for a client;

Fig. 4 is a view showing a format of a table for each type of process requests for a CSS server;

Fig. 5 is a view showing a format of a matrix table for managing a client status for a CSS server;

Fig. 6 is a view showing a format of a received data status for a CSS server;

Fig. 7 is a view showing a format of a transmission and receive data set for a CSS server;

Fig. 8 is a view showing a format of a transmission data set for a multimedia server;

Fig. 9 is a view showing a format of a matrix table for managing a CSS status for a multimedia server;

0966554-092100

Fig. 10 is a view showing a list of objects to be served for a CSS server;

Fig. 11 is a view showing a format of objects to be served for a multimedia server;

5 Fig. 12 is a flowchart (part 1) showing a processing operation of a system for transferring multimedia information according to an embodiment of the present invention; and

10 Fig. 13 is a flowchart (part 2) to be combined with the flowchart of Fig. 12, showing a processing operation of a system for transferring multimedia information according to an embodiment of the present invention.

DESCRIPTION OF THE PREFERRED EMBODIMENTS

15 Hereafter, the description will be oriented to a system for transferring multimedia information according to an embodiment of the present invention.

a In Fig. 1, a numeral 1 denotes a matrix table for managing a CSS status. A numeral 2 denotes a multimedia server. A numeral 3 denotes a disk unit for storing a data set to be transmitted. Numerals 4, 9, 18, 23, 26²⁹, and 32 denote LAN adapters provided with network addresses dedicated for transmission. Numerals 5, 8, 17, 22, 25, 28 and 31 denote LAN adapters provided with network addresses dedicated for receive. A numeral 6 denotes a communication network, ^{Specifically} ~~concretely~~ a wide area network (WAN) which is larger in scale than the LAN. Numerals 7, 36, and 37

a

001260-15599960

a
a

Moreover, the network addresses dedicated for transmission of the LAN adaptors 4, 9, 18, 23, 26, 29 and 32 may be made to be identical with the network addresses dedicated for receive of the LAN adaptors 5, 8, 17, 22, 25, 28 and 31. That is, one LAN adaptor having a single network address may have both of the transmitting and receiving functions.

The system according to an embodiment of the invention, as shown in Fig. 1, includes devices on the multimedia server side for backing up the CSS and a plurality of devices on the CSS side coupled through the network 6 such as the WAN and LAN devices 37, 7 and 36.

The devices on the multimedia server side includes the multimedia server 2 for backing up the CSS, the matrix table 1 for managing the statuses of the processes requested by the CSS side coupled to this server 2 and of the processed result data, a disk device 3 for storing a data set of the processed result to be

transmitted to the CSS side, a service list 34 where the CSS's to be served are registered at network addresses dedicated for the outputs, and the LAN adaptors 4 and 5 coupled to the LAN device 37.

5 One of the devices on the CSS side is arranged to have the CSS server 10 and the clients 14 and 19 coupled through the LAN adaptors 8, 9, 17, 18, 22, and 23 and the LAN device 7. The CSS server 10 is coupled to the disk device 11 for storing a data set of the processed result
10 received from the multimedia server 2 and another data set to be transmitted to the client, a received data status 12, a table for each type of processed request, and the service list 33. The clients 14 and 19 are coupled to the disk devices 15 and 20, ^{respectively,} for storing the data sets of the
15 processed result received from the multimedia server 2 and the received data statuses 16 and 21. The CSS server 24 and the clients 27 and 30 on the CSS side have the same arrangement as the foregoing devices on the CSS side.

In turn, the description will be oriented to the
20 formats of the tables, the lists, the statuses and the like coupled to the foregoing multimedia server 2, the CSS server 10, and the clients 14 and 19, respectively, with reference to the appended drawings.

The received data statuses 16 and 21 coupled to
25 the clients 14 and 19 are referenced and updated when the client requests the CSS server to ^{perform} ~~do~~ a process and receive the data ^{blocks} ~~block~~ of the processed result. As shown in Fig. 2, the status 16 or 21 is composed of network addresses 40

09665554.092100

a

a

to 43 dedicated for input and output of the CSS server and the subject client, a process request date 44, a process request time 45, a process request ID 46, a status update flag 47, and receive flags 48 to 50 for the first to the N-
5 th data blocks (N is an integer of 2 or more).

The network addresses 40 to 43 may use a single common network address ^{for} ~~to~~ transmission and ^{receipt of data} ~~receive~~ in place of the network addresses dedicated for transmission and receive.

10 The ^{received} data set ~~for receive~~ registered in the harddisk 15 or 20 has a format ^{including} ~~composed of~~ header information 51 and the first to the N-th data blocks 52 to 54 as shown in Fig. 3. The header information 51 ^{includes} ~~is~~ ~~composed~~ of network addresses 55 to 58 dedicated for inputs
15 and outputs of the CSS server and the subject client, the process request date 59, the process request time 60, and the process request ID 61, which format is the same as that described with reference to Fig. 2.

Each data block includes n (n is an integer of 1
20 or more) data units 200 and a header 201 at the head of the data. The header 201 contains a data block number and a data unit number stored as address information.

The table for each type of process request 35 coupled to the CSS server 10, as shown in Fig. 4, enables
25 ^{the storage of} ~~to store~~ m (m is an integer of 1 or more) pieces of information 62 to 65 for each type of process ^{request} ~~requests~~.
Each piece of information for each type of process request

a includes
is composed of a process request ID 66 of a client, a
backup processing flag 67, and a maximum value of a service
time of the CSS server.

a The matrix table 13 for managing a client status
5 coupled with the CSS server 10, as shown in Fig. 5, enables
the storage of
to store m pieces of status information 69 to 72 for the
process requests given by the clients. Each status
a information includes
is composed of network addresses 73 to 76
dedicated for inputs and outputs of the CSS server and the
10 clients, which are similar to the network addresses
described with reference to Fig. 2, a process request date
77, a process request time 78, a process request ID 79, and
receive flags 81 to 83 for the first to the N-th data
blocks. The different aspect
respect of Fig. 5 from Fig. 2 is, the
15 provision of a transfer completion flag 80 in place of a
status update flag.

001260 15599900
a The received data status 12 coupled to the CSS
server 10, as shown in Fig. 6, is composed of network
addresses 84 to 89 dedicated for inputs and outputs of the
20 multimedia server, the CSS server, and the clients, a
process request date 90, a process request time 91, a
process request ID 92, a status update flag 92, and receive
flags 94 to 96 for the first
first to the N-th data blocks.

a The data set for transmission and reception of data
receive,
25 registered in the disk device 11 coupled to the CSS server
10, has such a format as shown in Fig. 7. The format is
includes
composed of a header information 97 and the first to the N-
th data blocks 98 to 100. The header information 97 includes
is

9

10

h

a

a

096654-02100

a the storage of

~~to store~~ m pieces of status information 123 to 126 for the process requests given by the CSS servers as shown in Fig.

a 9. Each status information ^{has} ~~is the~~ similar composition to that ~~as~~ described with reference to Fig. 5. That is, each *a* status information ^{includes} ~~is composed~~ of network addresses 127 to *a* 5

132 dedicated for inputs and outputs of the CSS servers, the clients and the multimedia server, a process request date 133, a process request time 134, a process request ID 135, a transfer completion flag 136, and receive flags 137 10 to 139.

a The service list coupled to the CSS server side, as shown in Fig. 10, enables ^{the storage of} ~~to store~~ n network addresses 180 to 183 dedicated for outputs of the clients served by the subject CSS server.

15 The service list 34 coupled to the multimedia server 2, as shown in Fig. 11, enables ^{the storage of} ~~to store~~ n network *a* addresses 184 to 187 dedicated for outputs of the CSS servers served by the subject multimedia server 2.

As set forth above, according to an embodiment of 20 the invention, the system configured of the multimedia server, the CSS server and the clients is arranged to simplify a transmitting process between the multimedia server and the CSS server and the receiving process between the CSS server and the clients and solve the bottleneck in 25 networking between the multimedia server and CSS servers and between the CSS server and the clients for the purpose of quickly and efficiently transferring the data.

007260-1559960
0966554-092100

In turn, the description will be oriented to the operation of transferring the multimedia information in the system according to the foregoing embodiment of the invention with reference to Figs. 12 and 13. In this
5 embodiment of the invention, the clients, the CSS server and the multimedia server are operated independently of one another. Further, the multimedia server operates to back up the process executed by the CSS server. In response to the request given from the CSS server, the multimedia
10 server operates to transfer the multimedia information generated by the multimedia server itself to the CSS server. Further, the CSS server operates to transfer the received multimedia information to the client for requesting the multimedia information.

15 At first, the processing on the client side will be described.

(1) Now, assume that a process request is issued for transferring the multimedia information to the multimedia server 2. In response to the request, the
20 client 14 operates to set a process request status to the received data 16 and waits for the processed result data transferred from the CSS server 10 (steps 140 and 141).

(2) As will be described below, the CSS server 10 performs the process requested by the client 14 or
25 entrusts the process to the multimedia server 2. After obtaining the data of the processed result, the CSS server 10 or the multimedia server 2 operates to transfer the data to the client 14. The data of the processed result is

007260-4559960

divided into N data blocks, and each group of n data units of each data block is transferred back to the client 14 in sequence. The client 14 receives the processed result at each group of n data units (step 142).

5 (3) The process is executed for registering the processed result data received from the CSS server 10 in the harddisk 15 for storing the data set for receive (step 143). The received data status 16 is updated according to the receive status of the processed result data of the client 14 (step 144). ^{Specifically} ~~Concretely~~, the data block receive flags for the statuses 48, 49, 50 and the like as shown in Fig. 2 are set, and the status update flag 47 is set as well.

When all n data units contained in one data block are received, in response to the display request from the display unit 38, n pieces of data units are displayed on the screen (steps 146 and 147). ^{When} ~~In a case that~~ the image information is displayed, ^{as in} ~~like~~ the playback of a video disk, for example, the image section at any position is selectively displayed by specifying an address. Further, the still playback, the fast ^{forwarding} ~~feeding~~ or the reversing are also made possible.

(4) It is checked if all N data blocks are received. If it is not completed, the process from the step 142 is repeated (step 145).

(5) In the check at the step 145, if the receipt of all N data blocks is completed, the process is terminated.

007260-15599960

In addition, the client 14 enables to display the received data concurrently with the receipt of each group of n data units.

Next, the description will be oriented to the
5 process executed by the CSS server.

(6) The CSS server 10 operates to sequentially read the received data statuses 16 and 21 of the client where the client itself sets the process request at the step 141 as referring to the service list 33 (step 148).

(7) After reading the received data status 16 set by the client 14 for the purpose of the process request at the step 141, the CSS server 10 operates to add the network address 40 dedicated for an input of the CSS server, the network address 41 dedicated for an output of the CSS server, the network address 42 dedicated for an input of the client, the network address 43 dedicated for an output of the client, the process request date 44, the process request time 45, and the process request ID 46, all of which are shown in Fig. 2, to the matrix table 13 for managing the client status as the data items 73 to 79 shown in Fig. 5. If the received data status 16 has no content, the record of the fact is added to the matrix table 13 (step 149).

(8) By reading the table 35 for each type of process request, it is checked if the request for the process is to be backed up by the multimedia server (steps 150 and 151).

a

determined

15

20

25

[illegible]

and waits for the processed result data transferred from the multimedia server 2 (step 158).

(13) As will be described below, the multimedia server 2 performs the process requested by the CSS server 10 and, if the processed result data is obtained, transfers the data to the CSS server 10. The processed result data is divided into N data blocks, and each group of n data units contained in each data block is transferred to the CSS server one group by one group. The CSS server 10 receives the processed result at each group of n data units (step 159).

(14) The CSS 10 server performs a process for registering the processed result data received from the multimedia server 2 in the harddisk 11 for storing the data set for transmission and receive (step 160). Then, the CSS server 10 ^{updates} ~~operates to update~~ the received data status 12 according to the processed result data received status of the CSS server 10 itself (step 161). ^{Specifically} ~~Concretely~~, the data block receive flags for the statuses 94, 96, 96 and the like shown in Fig. 6 are set and the status update flag 93 is set as well.

If all n data units are received in one data block at a step 161, the operation goes to a step 155, at which the content of the matrix table for managing the client status shown in Fig. 5 is read.

(15) It is checked that the receipt of all N data blocks is completed. If not completed, the process

001250-15599960

a

a

from the step 159 is repeated (step 162). If all N data blocks are received, the process is terminated.

(16) At a step 154 (see Fig. 12), the data of the processed result given by the subject CSS server 10 is registered in the harddisk 11 for storing the data set for ~~transmission and receive~~ ^{transmitting and receiving}. On the termination of the process, the matrix table 13 for managing the client status shown in Fig. 5 is read in sequence (step 155).

(17) If a transfer completion flag 80 in the matrix table 13 for managing the client status is set and all the receive flags from the first to the N-th data block receive flags 81 to 83 are set, the corresponding records are deleted from the matrix table 13 for managing the client status, and the process is terminated (steps 156 and 157).

(18) If it is determined that the transfer completion flag 80 is off by referring to the matrix table 13 for managing the client status, the process for transmitting standby data blocks at each group of n data units is executed by repeating the process from the step 155. On the termination of transferring all N data blocks, the transfer completion flag 80 is set (step 163).

(19) The received data statuses 16 and 21 updated by the client 14 at the step 144 are read in sequence (step 164).

(20) The content of the received data status 16 is checked. If the status update flag 47 is set, the matrix table 13 for managing the client status is updated

007260-1599960

and if the transfer of the N data blocks is terminated, the transfer completion flag 80 is set. If the flag 47 has been already off, nothing is executed (step 165).

Of the foregoing processes of the CSS server, the
5 processes at the steps 155 to 157 and 163 are executed in parallel to and independently of the processes at the steps 164 and 165.

In turn, the description will be oriented to the process of the multimedia server.

10 (21) The multimedia server 2 operates to sequentially read the received data status 12 of the CSS server where the process request is set by the CSS server itself at the step 158 by referring to the service list 34 (step 166).

15 (22) The multimedia server 2 operates to read the received data status 12 of the client set by the CSS server 10 for the process request at the step 158 and to add a record composed of the network address 127 dedicated for an input of the multimedia server, the network address
20 dedicated for an output of the multimedia server, the network address 129 dedicated for an input of the CSS server, the network address 130 dedicated for an output of the CSS server, the network address 131 dedicated for an input of the client, the network address 132 dedicated for
25 an output of the client, the process request date 133, the process request time 134, the process request ID (Identification Information) 135 to the matrix table 1 for managing the CSS status shown in Fig. 9. If the received

0066554 092100
001250 1559960

data status 12 has no content, the record of the fact is added. Then, the update flag 93 is off (step 167).

a
a
a
5 (23) In response to the process request issued by the CSS server 10, the multimedia server ^{Perform}~~operates~~ to ^{divide}~~perform~~ a backup operation, ^{registered}~~divide~~ the created multimedia information into N data blocks, and ~~register~~ them as a data set for transmission in the disk 3 (steps 168 and 169).

(24) The multimedia server operates to sequentially read the matrix table 1 for managing the CSS status shown in Fig. 9 updated at the step 167 (step 170).

a
15 (25) If the transfer completion flag 136 ^{included}~~contained~~ in the matrix table 1 for managing the CSS status is set and all receive flags from the first to the N-th data block receive flags 137 to 139 are set, the corresponding records are deleted from the matrix table 1, and then the process is terminated (steps 171 and 175).

(26) If it is determined that the transfer completion flag 136 is off by referring to the matrix table 1, the process for transmitting the standby data blocks to the corresponding CSS sever 10 at each group of n data units is executed by repeating the process from the step 170. On the termination of all N data blocks, the transfer completion flag 136 is set (step 172).

25 (27) The multimedia server operates to sequentially read the received data status 12 of the CSS server which is updated by the CSS server 10 at the step 161 (step 173).

001260-4559960

a (28) The content of the received data status 12 is checked. If the status update flag 93 is set, the multimedia server ^{updates} ~~operates to update~~ the matrix table 1 for managing the CSS status. If the transfer of all N data 5 blocks is completed, the transfer completion flag 136 is off. If the flag 136 has been already off, nothing is executed (step 174).

Of the foregoing processes of the multimedia server, the processes at the steps 170 to 172 are executed 10 in parallel to and independently of the processes at the steps 173 and 174.

0966554.092100
a 15 In the foregoing embodiment of the invention, the client for issuing the process request is just required to receive the multimedia information from the multimedia server at the address defined on the ^{receives} ~~receive~~ side and set each group of n data units to the address. As mentioned above, the multimedia information is the result processed by the multimedia server. The multimedia information is divided into N data blocks and is transferred at each group 20 of n data units of each data block. Further, the streams of the multimedia information are allowed to be displayed concurrently ~~with~~ when those streams are stored. The storage of streams, ^{of multimedia data} at each group of n data units being received is executed in parallel with and concurrently with 25 the display of one previous received group of n data units. Like the playback of the video disk, the client thus provides a capability of controlling a fast feed, a stop, a

a

a

a

As set forth above, according to the present invention, the data of the result processed by the multimedia server is divided into N data blocks and each group of n data units of each data block is transferred to the address defined by the receiving side. The multimedia

5 request from the client.

server and the CSS servers and between the CSS server and the clients. Further, according to the present invention, only the side for transmitting the processed result data, such as the multimedia server or the CSS server, operates to transmit the data. Hence, the CSS arrangement may be dynamically changed. Besides, even in this case, the present invention offers an effect that the client side does not need any modification.

INSA2